



MATIERE : ACIER RESSORT

POUR ASSEMBLAGE PAR VIS METRIQUES

Ø DE VIS	Formes *	Epaisseur de tôle p	Références	Dimensions			
				a	b	c (+/- 0.3)	s
M3	C	0.8-1.6	49/U3 - 503	12	8	6	0.30
M4	C	0.6-2.5	49/U4 - 601	16	10	7	0.40
	C	1.0-2.0	49/U4 - 501	18		8.5	
	C	3.0-4.0	49/U4 - 520	17.5		7	
M5	N	0.6-1.1	49/U5 - 2212 -1	15	12	6.5	0.50
	B	0.6-1.4	49/U5 - 521-1	21		9.5	
	B	0.6-1.4	49/U5 - 509-1	24		12.5	
	N	1.2-1.8	49/U5 - 2212 -2	15		6.5	
	B	1.5-2.6	49/U5 - 521-2	21		9	
	B	1.5-2.6	49/U5 - 509 -2	24		12	
	N	1.9-2.2	49/U5 - 2212 -3	15		6	
N	2.3-3.0	49/U5 - 2212 -4	14.7	5.5			
M6	A	1.0-1.8	49/U6 - 2219 - 2	16.5	-	8.4	0.50
	A	1.9-3.0	49/U6 - 2219 - 3	16.2	16	7.4	
	C	2.0-3.2	49/U6 - 506	-	-	10	
	C	3.3-4.6	49/U6 - 516	24.5	14	9	

* voir fiche technique référence 49/FORMES